ARMY RESEARCH LABORATORY



Electrothermal-Chemical (ETC) Temperature Sensitivity of JA2 7 Perf Propellant

M. Del Guercio
I. Stobie
W. Oberle

ARL-TN-67 June 1996

DISCLAIMER NOTICE



THIS DOCUMENT IS BEST QUALITY AVAILABLE. THE COPY FURNISHED TO DTIC CONTAINED A SIGNIFICANT NUMBER OF PAGES WHICH DO NOT REPRODUCE LEGIBLY.

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1. AGENCY USE ONLY *(Leave blank)*	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED
	June 1996	Final, 1–31 March 1995

4. TITLE AND SUBTITLE
Electrothermal-Chemical (ETC) Temperature Sensitivity of JA2 7 Perf Propellant

5. FUNDING NUMBERS
PR: 1L162618AH80

6. AUTHOR(S)
M. Del Guercio, I. Stobie, and W. Oberle

7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)
U.S. Army Research Laboratory
ATTN: AMSRL-WT-PA
Aberdeen Proving Ground, MD 21005-5066

8. PERFORMING ORGANIZATION REPORT NUMBER
ARL–TN–67

9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)

10. SPONSORING / MONITORING AGENCY REPORT NUMBER

11. SUPPLEMENTARY NOTES

12a. DISTRIBUTION / AVAILABILITY STATEMENT
Approved for public release; distribution is unlimited.

12b. DISTRIBUTION CODE

13. ABSTRACT *(Maximum 200 words)*

The temperature sensitivity of JA2 7 perf propellant was studied by conditioning it to 21.1° C, 48.9° C, and -31.7° C. The firings were conducted in a 120-cc closed chamber, conventionally and with plasma injection (ETC), using a 1.2-ms pulse width provided by four banks of a 400 kJ PFN (Pulse Forming Network). The study showed a decrease in the burn rate between the ETC firings at 21.1° C and the conventional at the same temperature, but it showed an increase in the burn rate for the 48.9° C and -31.7° C cases, respectively.

14. SUBJECT TERMS	15. NUMBER OF PAGES
electrothermal-chemical, propellant, JA2 7 perf propellant, sensitivity	55
	16. PRICE CODE

17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	SAR

INTENTIONALLY LEFT BLANK.

TABLE OF CONTENTS

INTENTIONALLY LEFT BLANK.

LIST OF FIGURES

Figure Page

1. BACKGROUND

Electrothermal and Chemical (ETC) closed chamber firings in support of the US Army's ETC propulsion technology program using JA2, 7 perf propellant (RAD-PE-792-71), were conducted in April 1995. These firings used a 400 kJ upgraded pulse forming network (Del Guercio et al. 1995) to determine the temperature sensitivity of the propellant. A modified configuration consisting of four banks was used instead of the full eight banks (eight capacitors and eight inductors), with the purpose of using a shorter 1.2 ms pulse length instead of the full 2.4 ms. To obtain an energy output in the range of 20 kJ, a charging voltage of 4 kV was selected (Del Guercio et al. 1996).

2. EXPERIMENTAL FIRINGS

Nine firings were conducted in this series. The first six consisted of three pairs of ETC firings done at three different temperature ranges; 21.10° C, 48.9° C, and -31.7° C. They will be referred to as "ambient" plasma, "hot" plasma and "cold" plasma firings. The last series of three firings consisted of the baselines for the previous six, and were comprised of conventional firings (via electric match ignition and FFFG black powder pellets), fired at the same temperatures (i.e., 21.1° C, 48.9° C, and -31.7° C). The firing information sheets for these firings are included in Appendix C. Experimental pressure and PFN energy are shown in Appendix D, and the actual burn rate data are shown in Appendix E.

3. SUMMARY OF RESULTS

The three baseline tests obtained through conventional firings (non-ETC firings), idents 04255S7 at 21.1° C, 04265S8 at -31.7° C and 04275S9 at 48.9° C are shown in Figure 1. These plots indicate that for the conventional firing the burning rate of the propellant depends on its conditioning temperature, as the ambient locus is displayed between the hot and the cold.



Figure 1. Conventional firings at 21.1° C, 48.9° C, and -31.7° C.

The plasma firings (ETC firings) done at "ambient" (21.1° C), hot (48.9° C) and cold (-31.7° C) temperatures, correspond to the idents 04115S1 and 04115S2 for ambient, 04125S3 and 04175S4 for hot, and 04205S5 and 04205S6 for cold, respectively.

Burn rates for the plasma firings performed at "ambient" temperature (21.1° C) are plotted vs. the conventional firing at the same temperature (Figure 2). The "ambient" plasma burn rates (idents 04115S1 and 04115S2) show a decrease with respect to the "conventional" burn rate baseline at 21.1° C (ident 04255S7).

Burn rates for the "hot" plasma firings performed at 48.9° C (idents 04125S3 and 04175S4) are plotted along with the "conventional" burn rate at the same temperature (ident 04275S9) on Figure 3. An enhancement of the burn rates for the plasma "hot" tests can be observed with respect to the "conventional" baseline at the same temperature.

Burn rates for the "cold" plasma (-31.7° C) firings are plotted (idents 04205S5 and 04205S6) vs. the "conventional" burn rate at the same temperature (ident 04265S8) in Figure 4. Also in



Figure 2. "Ambient" plasma burn rates vs. "ambient" conventional.



Figure 3. "Hot" plasma burn rates vs. "hot" conventional.

this case, an enhancement on the burn rates for the "cold" test can be observed with respect to the "conventional" burn rate baseline at the same temperature.

To compare the effects of plasma injection on the propellant conditioned at the three different temperatures, burn rate change vs. pressure is plotted as:

1) "Ambient" plasma(21.1° C) burn rate vs. "conventional" burn rate baselines at 21.1° C and 48.9° C (Figure 5).

2) "Hot" plasma (48.9° C) burn rate vs. "conventional" burn rate baselines at 21.1° C and 48.9° C (Figure 6).

3) "Cold" plasma (-31.7° C) burn rate vs. "conventional" burn rate baselines at 21.1° C and -31.7° C (Figure 7).



Figure 4. "Cold" plasma burn rates vs. "cold" conventional.



Figure 5. "Ambient" plasma vs. "conventional" at 21.1° C and 48.9° C.



Figure 6. "Hot" plasma vs. "conventional" at 21.1° C and 48.9° C.



Figure 7. "Cold" plasma vs. "conventional" at 21.1° C and -31.7° C.

4. CONCLUSIONS

The burn rate percent differences between the "ambient" plasma (Figure 5) and the "ambient" conventional baseline is 14% (negative). The burn rate percent difference between the "hot" plasma (Figure 6) and the "hot" conventional baseline is 11.5%, while the burn rate percent difference between the "cold" plasma (Figure 7) and the "cold" conventional baseline is about 11.2%.

The injection of the "hot" plasma at 48.9° C (Figure 6) shows a more enhanced burn rate than the "cold" plasma firing at -31.7° C (Figure 7), while Figure 5 shows no enhancement at all for the "ambient" plasma injection.

The burn rate obtained for the "ambient" plasma injection agrees with previous data (Fortier et al. 1992) in which no noticeable effect has been observed for ETC firings at room temperature.

The increase on the burn rates for the "hot" plasma injection and the "hot" conventional cases, could be explained as related to the added energy used to condition the propellant up to 48.9° C.

One possible scenario for the behavior of the "cold" plasma (-31.7° C) firing, could be the fragmentation of the cold conditioned propellant as is impacted by the pressure waves and the initial plasma jet. This fragmentation would cause an increase in the propellant surface area which will then cause an increase in the apparent burning rate. Further tests will determine the repeatability of the "cold" conventional below the "ambient" conventional baseline.

INTENTIONALLY LEFT BLANK.

5. REFERENCES

Del Guercio, M., H. Burden, I. Stobie, and K. White. "A Pulse-Forming Network Design for Electrothermal-Chemical (ETC) Combustion Characterization of Solid Propellants." ARL-MR-261, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, September 1995.

Del Guercio, M., I. Stobie, and W. Oberle. "JA2 Firings With Modified 400 kJ Pulser." ARL-TN-66, U.S. Army Research Laboratory, Aberdeen Proving Ground, MD, May 1996.

Fortier, S., K. White, A. Juhasz, M. Del Guercio, and G. Katulka. "Combustion Characterization of Plasma-Augmented ETC Solid Propellants." 29th JANNAF Combustion Subcommittee Meeting, Hampton, VA, October 1992.

INTENTIONALLY LEFT BLANK.

APPENDIX A:

CONVENTIONAL AND ETC SETUP

FOR 120 CM^3 CLOSED CHAMBER

INTENTIONALLY LEFT BLANK.

The pulse forming network (PFN) configuration used for the closed chamber plasma injection uses only four banks (four capacitor-inductor sets) of the eight available. The pulse obtained is close to the 1.2-ms width desired. Figure A-1 schematic shows two of the banks and the PFN and closed vessel layout. Instrumentation for the conventional firing is shown in Figure A-2, where electric match ignition is obtained through an "impulse" firing box and data is recorded on the oscilloscopes through fiber optic links. Plasma injection (ETC) is obtained by discharge of the energy stored in the PFN as its closing switch (ignitron) is activated by a trigger signal. The configuration for ETC data acquisition is shown in Figure A-3.



Figure A-1. ETC closed vessel and PFN layout.



Figure A-2. Conventional mode data acquisition layout.



Figure A-3. ETC mode data acquisition layout.

APPENDIX B:

TEST FIRING MATRIX

INTENTIONALLY LEFT BLANK.

Table B-1 below, shows the sequence of the firings according to the order they were conducted. The conventional firings show zero electrical energy (kJ), zero electrical energy density (kJ/g), and zero pulse forming network (PFN) charging voltage (kV).

Table B-1. JA2 7 Perf Temperature sensitivity firings

ID No.	Loading Density (g/cm^3)	Temp (C°)	Energy (kJ)	Electrical Energy Density (kJ/g)	PFN Charging Voltage (kV)
04115S1	0.22	21.1	21	0.78	4
04115S2	0.22	21.1	21	0.78	4
04125S3	0.22	48.9	22	0.82	4
04175S4	0.22	48.9	21	0.78	4
04205S5	0.22	-31.7	24	0.89	4
04205S6	0.22	-31.7	23	0.86	4
04255S7	0.23	21.1	0	0	0
04265S8	0.22	-31.7	0	0	0
04275S9	0.22	48.9	0	0	0

INTENTIONALLY LEFT BLANK.

APPENDIX C:

FIRING INFORMATION DATA SHEETS

INTENTIONALLY LEFT BLANK.

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/11/95 SERIES RUN=: 1 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT =:RAD-PE-792-71 SAMPLE TREATMENT: 70F
SAMPLE WEIGHT:26.934g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC=:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
pfn's ROGOVSKI#2CAL K:82.45E-06;vessel's ROGOVSKI#1CAL K:80.49E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****
CAL (DC)VOLTAGE IN :NA
DISK ID:___ETC#4_____
TRACKID:_____

CAL#1(gage#1)/CHAN 1A: NA
VCAL VOLTAGE OUT:_____

CAL#2(gage#2)/CHAN 1B:NA
CAL VOLTAGE OUT:_____

*****SCOPE B*****
CAL (DC)VOLTAGE IN:8.0 V
DISK D: 120cc#4
TRACK ID:6

CAL#1(gage#1)/CHAN 1A:8.0 V
CAL VOLTAGE OUT: 9.28V

CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT: 9.07 V

FIRING

***** SCOPE A*****
DISK ID:ETC#4
TRACK ID:2
SENSITIVITY: MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt
1B: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt
2B: V	4ms	1usxpnt

ROGOVSKY#1 (m.A/V.s):1

PRESSURE MAX(MPa):150
SCOPE ID:B
GAGE ID: #1

*****SCOPE B*****
DISK ID:120cc#4
TRACK ID:7
SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE
1A: P1	8.0ms	2usxpnt
2A: P2	20ms	5usxpnt
2A: NA		
1B: ROGOSVKY#2		

ROGOSVSKY#2 (m.A/V.s):2

PRESSURE MAX(MPa):280
SCOPE ID:B
GAGE ID:#2

NOTES:
1 wrap of cellophane tape
27.346g total weigth

opaque grease in both gage ports

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/11/95 SERIES RUN=: 1 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT =:RAD-PE-792-71 SAMPLE TREATMENT: 70F
SAMPLE WEIGHT:26.889g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC=:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
pfn's ROGOVSKI#2CAL K:82.45E+06;vessel's ROGOVSKI#1CAL K:82.56E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****
CAL (DC)VOLTAGE IN :NA
DISK ID:___ETC#4_____
TRACKID:_____

CAL#1(gage#1)/CHAN 1A: NA
VCAL VOLTAGE OUT:_____

CAL#2(gage#2)/CHAN 1B:NA
CAL VOLTAGE OUT:_____

*****SCOPE B*****
CAL (DC)VOLTAGE IN:8.0 V
DISK D: 120cc#4
TRACK ID:8

CAL#1(gage#1)/CHAN 1A:8.0 V
CAL VOLTAGE OUT: 9.235V

CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT: 9.03 V

FIRING

***** SCOPE A*****
DISK ID:ETC#4
TRACK ID:3
SENSITIVITY: MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt
1B: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt
2B: V	4ms	1usxpnt

ROGOVSKY#1 (m.A/V.s)

PRESSURE MAX(MPa):260
SCOPE ID:B
GAGE ID:#1

*****SCOPE B*****
DISK ID:120cc#4
TRACK ID:9
SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE
1A: P1	8.0ms	2usxpnt
2A: P2	20ms	5usxpnt
2A: NA		
1B: ROGOSVKY#2		

ROGOSVSKY#2 (m.A/V.s)

PRESSURE MAX(MPa):270
SCOPE ID:B
GAGE ID:#2

NOTES: Sample weight : 26.889g
1 wrap of cellophane tape
27.311g total weigth

opaque grease in both gage ports

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/11/95 SERIES RUN#:3 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:120F
SAMPLE WEIGHT:26.946g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC#:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
vessel's ROGOVSKI#1CAL K:82:45E+06;pfn's ROGOVSKI#2CAL K:82.55E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****
CAL (DC)VOLTAGE IN :NA
DISK ID:___ETC#4_____
TRACKID:_____

CAL#1(gage#1)/CHAN 1A: NA
VCAL VOLTAGE OUT:_____

CAL#2(gage#2)/CHAN 1B:NA
CAL VOLTAGE OUT:_____

*****SCOPE B*****
CAL (DC)VOLTAGE IN:8.0 V
DISK D: 120cc#4
TRACK ID:10

CAL#1(gage#1)/CHAN 1A:8.0 V
CAL VOLTAGE OUT: 9.26V

CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT: 9.065 V

FIRING

***** SCOPE A*****
DISK ID:ETC#4
TRACK ID:4
SENSITIVITY: MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt
1B: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt
2B: V	4ms	1usxpnt

ROGOVSKY#1 (m.A/V.s)

PRESSURE MAX(MPa):260
SCOPE ID:B
GAGE ID:#1

*****SCOPE B*****
DISK ID:120cc#4
TRACK ID:11
SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE
1A: P1	8.0ms	2usxpnt
2A: P2	20ms	5usxpnt
2A: NA		
1B: ROGOSVKY#2		2usxpnt

ROGOSVSKY#2 (m.A/V.s)

PRESSURE MAX(MPa):270
SCOPE ID:B
GAGE ID:#2

NOTES: DATE : 04/12/95
1 wrap cellophane 27.329g total weigth
opaque grease in both gage ports

Previous firing got Rogosvky#1 replaced
At this firing Rogovsky #2 broke

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/11/95 SERIES RUN#:4 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:120F
SAMPLE WEIGHT:26.901g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC#:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
vessel's ROGOVSKI#1CAL K:82.34E+06;pfn's ROGOVSKI#2CAL K:82.56E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****
CAL (DC)VOLTAGE IN :NA
DISK ID:___ETC#4_____
TRACKID:_____

CAL#1(gage#1)/CHAN 1A: NA
VCAL VOLTAGE OUT:_____

CAL#2(gage#2)/CHAN 1B:NA
CAL VOLTAGE OUT:_____

*****SCOPE B*****
CAL (DC)VOLTAGE IN:8.0 V
DISK D: 120cc#4
TRACK ID:13

CAL#1(gage#1)/CHAN 1A:8.0 V
CAL VOLTAGE OUT: 9.230V

CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT: 9.025 V

FIRING

***** SCOPE A*****
DISK ID:ETC#4
TRACK ID:5
SENSITIVITY: MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt
1B: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt
2B: V	4ms	1usxpnt

ROGOVSKY#1 (m.A/V.s)

PRESSURE MAX(MPa):250
SCOPE ID:B
GAGE ID:#1

*****SCOPE B*****
DISK ID:120cc#4
TRACK ID:12
SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20.0ms	5usxpnt
2A: P2	20ms	5usxpnt
2A: NA		
1B: ROGOSVKY#2		5usxpnt

ROGOSVSKY#2 (m.A/V.s)

PRESSURE MAX(MPa):260
SCOPE ID:B
GAGE ID:#2

NOTES: DATE : 04/17/95
1 wrap cellophane 27.273g total weigth

vessel's side Rogovsky#1 defective

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/20/95 SERIES RUN#:5 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:-25F
SAMPLE WEIGHT:26.803g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC#:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
vessel's ROGOVSKI#1CAL K:80.79E+06;pfn's ROGOVSKI#2CAL K:82.56E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****	*****SCOPE B*****
CAL (DC)VOLTAGE IN :NA	CAL (DC)VOLTAGE IN:8.0 V
DISK ID:___ETC#4_____	DISK D: 120cc#4
TRACKID:_____	TRACK ID:14
CAL#1(gage#1)/CHAN 1A: NA	CAL#1(gage#1)/CHAN 1A:8.0 V
VCAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.295V
CAL#2(gage#2)/CHAN 1B:NA	CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.015 V

FIRING

***** SCOPE A*****	*****SCOPE B*****
DISK ID:ETC#4	DISK ID:120cc#4
TRACK ID:6	TRACK ID:15
SENSITIVITY: MIN	SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE	CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt	1A: P1	20.0ms	5usxpnt
1B: P2	20ms	5usxpnt	2A: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt	2A: NA		
2B: V	4ms	1usxpnt	1B: ROGOSVKY#2		
ROGOVSKY#1 (m.A/V.s)			ROGOSVSKY#2 (m.A/V.s)		

PRESSURE MAX(MPa):too low(190)	PRESSURE MAX(MPa):270
SCOPE ID:B	SCOPE ID:B
GAGE ID:#1	GAGE ID:#2

NOTES:
sample wrapped in cellophane,27.185g total weigth

new vessel's side Rogovsky#1 installed

ETCTEML1 INFORMATION SHEET FOR ETC CLOSED CHAMBER FIRING
DATE:04/20/95 SERIES RUN#:6 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:-25F
SAMPLE WEIGHT:26.812g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 290MPa WINDOW: 20ms

PFNPULSE LENGTH:1.2ms PFN SCHEMATIC#:4caps@830uF ea.&4ind@ 30uHea
PFN Vin DC:4.0kV; EXPECTED ENERGY:18.4kJ@ 70%efficy;WINDOW :4ms
PEARSON'S CAL K:2630;
vessel's ROGOVSKI#1CAL K:80.79E+06;pfn's ROGOVSKI#2CAL K:82.56E+06

MUZZLE GAGE#1 SN(P1): C47189 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.76E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****	*****SCOPE B*****
CAL (DC)VOLTAGE IN :NA	CAL (DC)VOLTAGE IN:8.0 V
DISK ID:___ETC#4_____	DISK D: 120cc#4
TRACKID:_____	TRACK ID:16
CAL#1(gage#1)/CHAN 1A: NA	CAL#1(gage#1)/CHAN 1A:8.0 V
VCAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.310V
CAL#2(gage#2)/CHAN 1B:NA	CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.025 V

FIRING

***** SCOPE A*****	*****SCOPE B*****
DISK ID:ETC#4	DISK ID:120cc#4
TRACK ID:7	TRACK ID:17
SENSITIVITY: MIN	SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE	CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt	1A: P1	20.0ms	5usxpnt
1B: P2	20ms	5usxpnt	2A: P2	20ms	5usxpnt
2A:di/dt	4ms	1usxpnt	2A: NA		
2B: V	4ms	1usxpnt	1B: ROGOSVKY#2 , 5usxpnt		
ROGOVSKY#1 (m.A/V.s)			ROGOSVSKY#2 (m.A/V.s)		

PRESSURE MAX(MPa):	PRESSURE MAX(MPa):270
SCOPE ID:B	SCOPE ID:B
GAGE ID:#1	GAGE ID:#2

NOTES:
sample wrapped in cellophane,27.145g total weigth

new vessel's side Rogovsky#1 worked fine.
gage #1 did not record

CONTML1 INFORMATION SHEET FOR CLOSED CHAMBER FIRING
DATE:04/25/95 SERIES RUN#:7 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:70F
SAMPLE WEIGHT:27.182g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 270MPa WINDOW: 20ms

MUZZLE GAGE#1 SN(P1): C20303 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.24E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****	*****SCOPE B*****
CAL (DC)VOLTAGE IN :NA	CAL (DC)VOLTAGE IN:8.0 V
DISK ID:___ NA _____	DISK D: 120cc#4
TRACKID:_____	TRACK ID:18
CAL#1(gage#1)/CHAN 1A: NA	CAL#1(gage#1)/CHAN 1A:8.0 V
VCAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.390V
CAL#2(gage#2)/CHAN 1B:NA	CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.13 V

FIRING

***** SCOPE A*****	*****SCOPE B*****
DISK ID: NA	DISK ID:120cc#4
TRACK ID:	TRACK ID:19
SENSITIVITY: MIN	SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE	CHANNEL	WINDOW	S.RATE
1A:			1A: P1	20ms	5usxpnt
1B:			2A: P2	20ms	5usxpnt
2A:			1B: NA		
2B:			2B: NA		

PRESSURE MAX(MPa):250	PRESSURE MAX(MPa):250
SCOPE ID:B	SCOPE ID:B
GAGE ID:#1	GAGE ID:#2

NOTES:
sample wrapped in cellophane,27.959g total weigth
0.575g FFFG, electric match

CONTML1 INFORMATION SHEET FOR CLOSED CHAMBER FIRING
DATE:04/26/95 SERIES RUN#:8 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf;LOT #:RAD-PE-792-71 SAMPLE TREATMENT:-25F
SAMPLE WEIGHT:27.182g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 270MPa WINDOW: 20ms

MUZZLE GAGE#1 SN(P1): C20303 SIDE GAGE#2 SN(P2): C19928
gage#1:1rstdegfit coeff:5.24E-02;gage#2:1rstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****	*****SCOPE B*****
CAL (DC)VOLTAGE IN :NA	CAL (DC)VOLTAGE IN:8.0 V
DISK ID:___ NA _____	DISK D: 120cc#5
TRACKID:_____	TRACK ID:#1
CAL#1(gage#1)/CHAN 1A: NA	CAL#1(gage#1)/CHAN 1A:8.0 V
VCAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.385V
CAL#2(gage#2)/CHAN 1B:NA	CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT:_____	CAL VOLTAGE OUT: 9.15 V

FIRING

***** SCOPE A*****	*****SCOPE B*****
DISK ID: NA	DISK ID:120cc#5
TRACK ID:	TRACK ID:#2
SENSITIVITY: MIN	SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE	CHANNEL	WINDOW	S.RATE
1A:			1A: P1	20ms	5usxpnt
1B:			2A: P2	20ms	5usxpnt
2A:			1B: NA		
2B:			2B: NA		

PRESSURE MAX(MPa):	PRESSURE MAX(MPa):230
SCOPE ID:B	SCOPE ID:B
	GAGE ID:#1
	GAGE ID:#2

NOTES:
sample wrapped in cellophane,27.593g total weigth
0.541g FFFG, electric match

CONTML1 INFORMATION SHEET FOR CLOSED CHAMBER FIRING
DATE:04/27/95 SERIES RUN#:9 PROJECT: 129.0 CLOSED CHAMBER
PROPELLANT TYPE:JA2;7perf:LOT #:RAD-PE-792-71 SAMPLE TREATMENT:120F
SAMPLE WEIGHT:27.060g GRAIN DIMENSION:0.6"L, 0.3"D; 0.03 WEB
CHAMBERVOL:129.4cc CALCMAX PRESSURE: 270MPa WINDOW: 20ms

MUZZLE GAGE#1 SN(P1): C20303 SIDE GAGE#2 SN(P2): C19928
gage#1:lrstdegfit coeff:5.24E-02;gage#2:lrstdegfit coeff:5.21E-02

CALIBRATION

*****SCOPE A*****
CAL (DC)VOLTAGE IN :NA
DISK ID:___ NA _____
TRACKID:_____

CAL#1(gage#1)/CHAN 1A: NA
VCAL VOLTAGE OUT:_____

CAL#2(gage#2)/CHAN 1B:NA
CAL VOLTAGE OUT:_____

*****SCOPE B*****
CAL (DC)VOLTAGE IN:8.0 V
DISK D: 120cc#5
TRACK ID:#3

CAL#1(gage#1)/CHAN 1A:8.0 V
CAL VOLTAGE OUT: 9.375V

CAL#2(gage#2)/CHAN 2A:8.0 V
CAL VOLTAGE OUT: 9.165 V

FIRING

***** SCOPE A*****
DISK ID: NA
TRACK ID:
SENSITIVITY: MIN

CHANNEL	WINDOW	S.RATE
1A:		
1B:		
2A:		
2B:		

PRESSURE MAX(MPa):
SCOPE ID:B

*****SCOPE B*****
DISK ID:120cc#5
TRACK ID:#4
SENSITIVITY:MIN

CHANNEL	WINDOW	S.RATE
1A: P1	20ms	5usxpnt
2A: P2	20ms	5usxpnt
1B: NA		
2B: NA		

PRESSURE MAX(MPa):
SCOPE ID:B
GAGE ID:#1
GAGE ID:#2

NOTES:
sample wrapped in cellophane,27.866g total weigth
0.563g FFFG, electric match

INTENTIONALLY LEFT BLANK.

APPENDIX D:

EXPERIMENTAL PRESSURE AND PULSE FORMING NETWORK ENERGY OUTPUT

INTENTIONALLY LEFT BLANK.



Figure D-1. Ident 4115S1 (ETC), pressure vs. time.



Figure D-2. Ident 4115S1 (ETC), energy vs. time.



Figure D-3. Ident 4115S2 (ETC), pressure vs. time.



Figure D-4. Ident 4115S2 (ETC), energy vs. time.



Figure D-5. Ident 4125S3(ETC), pressure vs. time.



Figure D-6. Ident 4125S3 (ETC), energy vs. time.



Figure D-7. Ident 4175S4 (ETC), pressure vs. time.



Figure D-8. Ident 4175S4 (ETC), energy vs. time.



Figure D-9. Ident 4205S5 (ETC), pressure vs. time.



Figure D-10. Ident 4205S5 (ETC), energy vs. time.



Figure D-11. Ident 4205S6 (ETC), pressure vs. time.



Figure D-12. Ident 4205S6 (ETC), energy vs. time.



Figure D-13. Ident 4255S7 (conventional), pressure vs. time.



Figure D-14. Ident 4265S8 (conventional), pressure vs. time.



Figure D-15. Ident 4275S9 (conventional), pressure vs. time.

APPENDIX E:

BURN RATES

INTENTIONALLY LEFT BLANK.

The BRLCB[1] code was used to obtain the ETC as well as the conventional burn rate analysis. The first six plots of burn rate vs. pressure correspond to the ETC firings, and the last three correspond to the conventional firings. Plots show burn rate vs. pressure on log-log axis.

[1] Oberle, W., and D. Kooker. "BRLCB: A Closed-Chamber Data Analysis Program." ARL-TR-36, U.S Army Research Laboratory, Aberdeen Proving Ground, MD, January 1993.


BURNING RATE PLØT 0411551.out
PRESSURE (MPa)
BURNING RATE (cm/s)
10^1
10^2
10^3
10^{-1}
10^0
2
3
4
5
6
7
8
9

```
                              ETC BURN RATE ANALYSIS
                                   BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04115S1.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04115S1.pvt           Calculation Output File: 04115S1.out
Smoothed: 04115S1.pdt           Graphics File          : 04115S1.dat
EE  File: A:04115S1E.AD
Fired on: 04/11/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY JA27PERF @ 70F
USED GAGE#2 AND 04115S2E.AD AS DI/DT DUE YO
FAULTY ROVGOSKY

                        IGNITER INFORMATION
The Igntier Used Is           : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)         :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)        :   1.75000 Gamma            :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                      PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information                Gage Information
-------------------------------------------------
Bomb Type     :Closed Chamber       Gage I.D.     : C19928
Bomb Vol (cc):      129.4           Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:   .21637E+00
                                    B:   .54171E-01
                                    C:  -.31853E-06

        Temperature and Charge Mass Information
-------------------------------------------------------
Propellant Mass (g)   :  26.9340      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  294.         Igniter Temp.(K):  294.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.49


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04115S1.OP7
 ********************************************************************************

 ********************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```


BURNING RATE PLOT 0411552.out
BURNING RATE (cm/s)
PRESSURE (MPa)
10^-1
10^0
10^1
10^2
10^3
2 3 4 5 6 7 8 9

```
                              ETC BURN RATE ANALYSIS
                                   BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04115S2.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04115S2.pvt           Calculation Output File: 04115S2.out
Smoothed: 04115S2.pdt           Graphics File          : 04115S2.dat
EE  File: A:04115S2E.AD
Fired on: 04/11/95
FIRING REMARKS:
TEMPERATURE SENSIVITY JA27PERF @ 70F
USED GAGE # 1 FOR REDUCTION

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                       PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                     PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information               Gage Information
-------------------------------------------------
Bomb Type    :Closed Chamber        Gage I.D.     : C47189
Bomb Vol (cc):     129.4            Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:   .66081E+00
                                    B:   .61167E-01
                                    C:  -.39696E-06

       Temperature and Charge Mass Information
-------------------------------------------------
Propellant Mass (g)   :  26.8890      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  294.         Igniter Temp.(K):  294.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.44


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04115S2.OP7
 ********************************************************************************

 ********************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```


BURNING RATE PLØT 041253.out
BURNING RATE (cm/s)
10^{-1}
10^{0}
10^{1}
10^{2}
10^{3}
2 3 4 5 6 7 8 9
10^{1}
10^{2}
10^{3}
PRESSURE (MPa)

```
                    ETC BURN RATE ANALYSIS
                         BRLCB V3.0
              ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB    Requested by          : DEL GUERCIO
Inf File: 04125S3.inf          Created From .MAS File : JA27PERF.MAS
P/T File: 04125S3.pvt          Calculation Output File: 04125S3.out
Smoothed: 04125S3.pdt          Graphics File         : 04125S3.dat
EE  File: A:04125S3E.AD
Fired on: 04/12/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY JA27PERF @ 120F
gage#2 used as gag2#1 was low

                  IGNITER INFORMATION
The Igntier Used Is          : Black Powder        Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                  PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                  PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information              Gage Information
-----------------------------------------------------
Bomb Type    :Closed Chamber       Gage I.D.    : C19928
Bomb Vol (cc):     129.4           Input Voltage:  8.0000
                                   Constants For Fit: A+Bx+C^2
                                   A:   .21637E+00
                                   B:   .54171E-01
                                   C:  -.31853E-06

       Temperature and Charge Mass Information
-----------------------------------------------------
Propellant Mass (g)   :  26.9460      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  322.         Igniter Temp.(K):  322.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.50


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04125s3.op7
 ********************************************************************************

 ********************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```


BURNING RATE PLOT 04175S4.out
BURNING RATE (cm/s)
10^{2}
10^{1}
10^{0}
10^{-1}
2 3 4 5 6 7 8 9
10^{1}
10^{2}
10^{3}
PRESSURE (MPa)

```
                              ETC BURN RATE ANALYSIS
                                    BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04175S4.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04175S4.pvt           Calculation Output File: 04175S4.out
Smoothed: 04175S4.pdt           Graphics File          : 04175S4.dat
EE  File: A:04175S4E.AD
Fired on: 04/17/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY JA27PERF @ 120F
USED GAGE#2 FOR REDUCTION

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                      PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information                Gage Information
-------------------------------------------------
Bomb Type     :Closed Chamber       Gage I.D.     : C19928
Bomb Vol (cc):     129.4            Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:   .21637E+00
                                    B:   .54171E-01
                                    C:  -.31853E-06

        Temperature and Charge Mass Information
-------------------------------------------------
Propellant Mass (g)   :  26.9010      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  322.         Igniter Temp.(K):  322.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.46


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04175S4.OP7
 ********************************************************************************

 ********************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```



BURNING RATE PLØT 04205S5.out
BURNING RATE (cm/s)
10^{-1}
10^{0}
10^{1}
10^{2}
10^{3}
PRESSURE (MPa)
2 3 4 5 6 7 8 9
2 3 4 5 6 7 8 9

```
                              ETC BURN RATE ANALYSIS
                                    BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04205S5.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04205S5.pvt           Calculation Output File: 04205S5.out
Smoothed: 04205S5.pdt           Graphics File          : 04205S5.dat
EE  File: A:04205S5E.AD
Fired on: 04/20/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY JA27PERF @ -25F
USED GAGE#2 FOR REDUCTION

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                     PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information               Gage Information
-----------------------------------------------------
Bomb Type    :Closed Chamber        Gage I.D.    : C19928
Bomb Vol (cc):     129.4            Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:   .21637E+00
                                    B:   .54171E-01
                                    C:  -.31853E-06

       Temperature and Charge Mass Information
-----------------------------------------------------
Propellant Mass (g)   :  26.8030      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  241.         Igniter Temp.(K):  241.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.36


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04205S5.OP7
 ********************************************************************************

 ********************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```


BURNING RATE PLØT 04205S6.out
BURNING RATE (cm/s)
PRESSURE (MPa)

```
                              ETC BURN RATE ANALYSIS
                                    BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04205S6.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04205S6.pvt           Calculation Output File: 04205S6.out
Smoothed: 04205S6.pdt           Graphics File          : 04205S6.dat
EE  File: A:04205S6.EGY
Fired on: 04/20/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY JA27PERF @ -25F
USED GAGE#2 FOR REDUCTION

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                      PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information               Gage Information
-------------------------------------------------------
Bomb Type    :Closed Chamber        Gage I.D.    : C19928
Bomb Vol (cc):     129.4            Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:   .21637E+00
                                    B:   .54171E-01
                                    C:  -.31853E-06

       Temperature and Charge Mass Information
-------------------------------------------------
Propellant Mass (g)   :  26.8120      Igniter Mass (g):    .0000
Initial Temp. Prop.(K):  241.         Igniter Temp.(K):  294.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.37


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04205S6.OP7
 ********************************************************************************************

 ********************************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000
```


BURNING RATE PLOT 042555S7.out
BURNING RATE (cm/s)
PRESSURE (MPa)

```
                              BURNING RATE ANALYSIS
                                BRLCB V3.0
                        ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04255S7.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04255S7.pvt           Calculation Output File: 04255S7.out
Smoothed: 04255S7.pdt           Graphics File         : 04255S7.dat
Fired on:

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder          Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                      PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information              Gage Information
-------------------------------------------------
Bomb Type    :Closed Chamber       Gage I.D.    : C20303
Bomb Vol (cc):     129.4           Input Voltage:  8.0000
                                   Constants For Fit: A+Bx+C^2
                                   A:  -.44711E+00
                                   B:   .54134E-01
                                   C:  -.17743E-06

        Temperature and Charge Mass Information
-------------------------------------------------
Propellant Mass (g)   :  27.9590      Igniter Mass (g):    .5750
Initial Temp. Prop.(K):  294.         Igniter Temp.(K):  294.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    26.46


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04255S7.OP7
 ********************************************************************************************

 ********************************************************************************************

     Total # Layers =    1

     Chamber Volume (cm3) =   129.400

     Heat-Loss-Fraction (n-d) =      .000

     Time Step (mil-sec) =   .10000000E-01     Max Time Steps =    1200

     Convergence Criterion =    .10000000E-04
```



BURNING RATE PLOT 0426558.out
BURNING RATE (cm/s)
PRESSURE (MPa)
10^{-1}
10^{0}
10^{1}
10^{2}
10^{3}
10^{1}
2 3 4 5 6 7 8 9
10^{2}
2 3 4 5 6 7 8 9
10^{3}

```
                              BURNING RATE ANALYSIS
                                    BRLCB V3.0
                          ADVANCED BALLISTIC CONCEPTS BRANCH - BRL


Project : 120CC CLOSED BOMB     Requested by          : DEL GUERCIO
Inf File: 04265S8.inf           Created From .MAS File : JA27PERF.MAS
P/T File: 04265S8.pvt           Calculation Output File: 04265S8.out
Smoothed: 04265S8.pdt           Graphics File         : 04265S8.dat
Fired on: 04/26/95
FIRING REMARKS:
TEMPERATURE SENSITIVITY CONV. FIRING
JA27PERF @ -25F, used gage#1

                        IGNITER INFORMATION
The Igntier Used Is          : Black Powder         Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

     IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g)        :     290.0 Molecular Weight  :  66.37000
Flame Temperature (K):    2188.0 Covolume (cc/g)   :    .78500
Density (g/cc)       :   1.75000 Gamma             :   1.21840

                      PROPELLANT INFORMATION
The Propellant Used Is          : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

 Propellant Thermochemical Properties: Following
 Sheets of Output

                      PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
          Length --- (cm.):  1.529080
          Outer Diam.(cm.):   .762000
          Perf Diam. (cm.):   .066040
          Inner Web  (cm.):   .130810
          Outer Web  (cm.):   .151130

     Bomb Information               Gage Information
-------------------------------------------------------
Bomb Type     :Closed Chamber       Gage I.D.     : C20303
Bomb Vol (cc):      129.4           Input Voltage:  8.0000
                                    Constants For Fit: A+Bx+C^2
                                    A:  -.44711E+00
                                    B:   .54134E-01
                                    C:  -.17743E-06

        Temperature and Charge Mass Information
-------------------------------------------------------
Propellant Mass (g)   :  26.7890      Igniter Mass (g):    .5410
Initial Temp. Prop.(K):  241.         Igniter Temp.(K):  294.
Initial Bomb Temp. (K):  294.
Number of Propellant Grains:    25.35


Number of Wildpoint Passes:   1 Wildpoint Tolerance:  5.000
Number of Smoothing Passes:   1 Smoothing Option:  1
Bridge Length: 15
1 OUTPUT FILE: 04265s8.op7
 ********************************************************************************************


 ********************************************************************************************


     Total # Layers =    1
```



BURNING RATE PLOT 0427559.out
PRESSURE (MPa)
BURNING RATE (cm/s)
10^1
10^2
10^3
10^-1
10^0
10^1
10^2
10^3

BURNING RATE ANALYSIS
BRLCB V3.0
ADVANCED BALLISTIC CONCEPTS BRANCH - BRL

Project : 120CC CLOSED BOMB Requested by : DEL GUERCIO
Inf File: 04275S9.inf Created From .MAS File : JA27PERF.MAS
P/T File: 04275S9.pvt Calculation Output File: 04275S9.out
Smoothed: 04275S9.pdt Graphics File : 04275S9.dat
Fired on: 04/27/95
FIRING REMARKS:
TEMPERSTURE SENSITIVITY, CONV. FIRING
JA27PERF @ 120F, gage#1 used.

IGNITER INFORMATION
The Igntier Used Is : Black Powder Lot: FFFG
The Source For The Igniter Is: Pellets, Milan Ord.

IGNITER THERMOCHEMICAL PROPERTIES:
Impetus (J/g) : 290.0 Molecular Weight : 66.37000
Flame Temperature (K): 2188.0 Covolume (cc/g) : .78500
Density (g/cc) : 1.75000 Gamma : 1.21840

PROPELLANT INFORMATION
The Propellant Used Is : JA-2 7-PERF GRANULAR Lot: RAD-PE-792-71
The Source For The Propellant Is: RADFORD ARMY AMMUNIT

Propellant Thermochemical Properties: Following
Sheets of Output

PROPELLANT GRAIN GEOMETRY

Grain Type:7-Perf. Cyl.
Length --- (cm.): 1.529080
Outer Diam.(cm.): .762000
Perf Diam. (cm.): .066040
Inner Web (cm.): .130810
Outer Web (cm.): .151130

Bomb Information		Gage Information	
Bomb Type	:Closed Chamber	Gage I.D.	: C20303
Bomb Vol (cc):	129.4	Input Voltage:	8.0000
		Constants For Fit:	A+Bx+C^2
		A:	-.44711E+00
		B:	.54134E-01
		C:	-.17743E-06

Temperature and Charge Mass Information

Propellant Mass (g) :	27.0600	Igniter Mass (g):	.5630
Initial Temp. Prop.(K):	322.	Igniter Temp.(K):	294.
Initial Bomb Temp. (K):	294.		
Number of Propellant Grains:	25.61		

Number of Wildpoint Passes: 1 Wildpoint Tolerance: 5.000
Number of Smoothing Passes: 1 Smoothing Option: 1
Bridge Length: 15
1 OUTPUT FILE: 04275s9.op7
****

****

Total # Layers = 1

Chamber Volume (cm3) = 129.400

INTENTIONALLY LEFT BLANK.

NO. OF COPIES	ORGANIZATION
2	ADMINISTRATOR ATTN DTIC DDA DEFENSE TECHNICAL INFO CTR CAMERON STATION ALEXANDRIA VA 22304-6145
1	DIRECTOR ATTN AMSRL OP SD TA US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145
3	DIRECTOR ATTN AMSRL OP SD TL US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145
1	DIRECTOR ATTN AMSRL OP SD TP US ARMY RESEARCH LAB 2800 POWDER MILL RD ADELPHI MD 20783-1145
	ABERDEEN PROVING GROUND
2	DIR USARL ATTN AMSRL OP AP L (305)

NO. OF COPIES ORGANIZATION

1 HQDA
ATTN SARD TR
K KOMINOS
PENTAGON
WASHINGTON DC 20310-0103

1 HQDA
ATTN SARD TR
R CHAIT
PENTAGON
WASHINGTON DC 20310-0103

1 DIRECTOR
ARMY RESEARCH OFFICE
ATTN AMXRO MCS K CLARK
PO BOX 12211
RESEARCH TRIANGLE PARK NC
27709-2211

1 DIRECTOR
ARMY RESEARCH OFFICE
ATTN AMXRO RT IP LIB SERV
PO BOX 12211
RESEARCH TRIANGLE PARK
27709-2211

ABERDEEN PROVING GROUND

126 DIR, USARL
ATTN: AMSRL-SC,
W. MERMAGEN
W. STUREK
AMSRL-SC-C, H. BREAUX
AMSRL-SC-CC,
J. GROSH
A. CELMINS
AMSRL-SC-S, A. MARK
AMSRL-SL-B, P. DEITZ (328)
AMSRL-SL-BA, J. MORRISSEY (433)
AMSRL-SL-BG, A. YOUNG (238)
AMSRL-SL-BL, M. RITONDO (328)
AMSRL-SL,BS, D. BELY (328)
AMSRL-SL-BV, R. SANDMEYER (247)
AMSRL-SL-I, M. STARKS (433)
AMSRL-WT,
D. ECCLESHALL
I. MAY
J. ROCCHIO
AMSRL-WT-P, A. HORST

NO. OF COPIES ORGANIZATION

AMSRL-WT-PA,
R. ANDERSON
A. BIRK
C. BULLOCK
A. BRANT
L-M. CHANG
T. COFFEE
J. COLBURN
P. CONROY
M. DEL GUERCIO (5 CP)
J. DESPIRITO
S. FORTIER
J. HEWITT
S. HOWARD
A. JOHNSON
A. JUHASZ
G. KATULKA
G. KELLER
M. KIWAN
J. KNAPTON
D. KOOKER
D. KRUCZYNSKI
C. LEVERITT
M. MCQUAID
T. MINOR
M. NUSCA
K. NEKULA
W. OBERLE
P. REEVES
M. RIDGLEY
T. ROSENBERGER
C. RUTH
I. STOBIE
P. TRAN
J. TUERK
K. WHITE
A. WILLIAMS
G. WREN
AMSRL-WT-PB,
M. BUNDY
P. PLOSTINS
AMSRL-WT-PC,
G. ADAMS
W. ANDERSON
R. BEYER
S. BUNTE
A. COHEN
R. FIFER

NO. OF COPIES ORGANIZATION

ABERDEEN PROVING GROUND (CONT)

AMSRL-WT-PC (CONT)
B. FORCH
J. HEIMERL
A. KOTLAR
M. MILLER
L. SEGER
A. MIZIOLEK
M. SCHROEDER
J. VANDERHOFF
S. MEDLIN
K. MCNESBY
N. FELL
J. WIDDER
J. MORRIS
S. NEWTON
R. PESCE-RODRIGUEZ
AMSRL-WT-PD,
A. ABRAHAMIAN
J. BENDER
B. BURNS
M. LEADORE
G. GAZONAS
R. LIEB
C. HOPPEL
L. BURTON
W. DRYSDALE
T. ERLINE
A. FRYDMAN
D. HOPKINS
R. KASTE
S. WILKERSON
AMSRL-WT-T, W. MORRISON
AMSRL-WT-TA,
M. BURKINS
W. GILLICH
AMSRL-WT-TB,
K. BENJAMIN
R. FREY
AMSRL-WT-TC,
W. DE ROSSET
B. SORENSEN
G. SILSBY
AMSRL-WT-TD, A. DIETRICH
AMSRL-WT-W, C. MURPHY
AMSRL-WT-WA,
A. BARAN
B. MOORE
H. ROGERS

NO. OF COPIES ORGANIZATION

AMSRL-WT-WB,
F. BRANDON
W. D'AMICO
AMSRL-WT-WC,
T. BROSSEAU
B. HAUG
AMSRL-WT-WD,
A. NIILER
F. PIERCE
AMSRL-WT-WE, J. THOMAS
AMSRL-MA, L. JOHNSON
AMSRL-MA-A,
J. PLUMER
K. BAMBERG
AMSRL-MA-P,
D. VIECHNICKI
R. SHULFORD
M. ROYLANCE
P. TOUCHET
AMSRL-MA-C,
T. HAYNES
W. ROY
R. ADLER
S. CHOU

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. ARL Report Number/Author ARL-TN-67 (Del Guercio) Date of Report June 1996

2. Date Report Received _____

3. Does this report satisfy a need? (Comment on purpose, related project, or other area of interest for which the report will be used.) _____

4. Specifically, how is the report being used? (Information source, design data, procedure, source of ideas, etc.) _____

5. Has the information in this report led to any quantitative savings as far as man-hours or dollars saved, operating costs avoided, or efficiencies achieved, etc? If so, please elaborate. _____

6. General Comments. What do you think should be changed to improve future reports? (Indicate changes to organization, technical content, format, etc.) _____

CURRENT ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

7. If indicating a Change of Address or Address Correction, please provide the Current or Correct address above and the Old or Incorrect address below.

OLD ADDRESS

Organization

Name

Street or P.O. Box No.

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)

(DO NOT STAPLE)